

# KORONÉ

Ventilated refrigeration island  
for display of fresh pre-packed product  
TN version with running temperature  $-1/+7^{\circ}\text{C}$

KORONÉ island plug-in, guarantees low consumption, wide display space  
and an optimum visibility of the product sell.



REFRIGERATION ARCHITECTURE



- Models available: 150, 200, 250
- High visibility of the products displayed
- Profiles and bumpers in PVC, personalisable
- Ventilated refrigeration
- Automatic defrosting
- Automatic evaporation system of condensing water
- Dividers for refrigerated unit (optional)
- Kit lateral side
- Available in three aesthetic solutions: standard, colours and fashion

RANGE OF COLOURS AVAILABLE: COLOURS AND FASHION



KORONÉ 200 COLOURS



KORONÉ 200 FASHION

KORONÉ 200 STANDARD

# KORONÉ

## DESIGN

KORONÉ is an island with an innovative design to display the product in a practical and functional way. Each part of Koronè has been designed to keep attention to aesthetics, without sacrificing the functionality.

## TECHNICAL

KORONÉ is produced with advanced technological solutions which guarantee finest performance and a durable life time.

## EFFICIENCY

The particular technical solutions allow to combine a high displaying capacity with limited dimensions. koronè is particularly suitable to the small and medium surfaces. The wide personalisable spaces make KORONÉ an item extremely valid to sell promotional products in big surfaces.


## QUALITY

To us quality means flexible projects, care on details and reliability throughout time. Such goals can be obtained only through professionalism and passion of hundreds of ISA men, continuously working to increase the levels of customers' satisfaction.

Ventilated refrigeration island  
for display of fresh pre-packed product  
TN version with running temperature  $-1/+7^{\circ}\text{C}$



REFRIGERATION ARCHITECTURE



KORONÉ



Grills and bottoms adjustable in height



Upper in metacrylate

## Technical characteristics

	150 TN	200 TN	250 TN
LxPxH mm	1540x1040x895	2040x1040x895	2540x1040x895
Capacity (gross/net) litres	548/261	743/354	938/445
Product temperature °C	-1/+7	-1/+7	-1/+7
Voltage v/Hz	230/50	230/50	230/50
Electrical input (standard) W/A	500/3.1	650/3.6	560/4.5
Electrical input (defrosting) W/A	1100/4.7	1400/6.0	1700/7.4
Defrosting	electrical	electrical	electrical
Net weight kg	115	163	188

Due to the quality advancement programmes and continuous scientific research ISA reserves the right to modify any technical specifications without notice.



ISA S.p.A.  
Via del Lavoro, 5  
06083 BASTIA UMBRA (PG) ITALY  
Tel. 075-80171 - Fax 075-8000900  
<http://www.isaitaly.com>

7/03413 C. 01 - 03/02